



Abbildung ähnlich

Product Features

LC-D/LC-D patch cord, OS2 APC, yellow, 5m

- MM-fibre, G50/125 Åm, grade C3 or SM-Faser E9/125Åm, grade C1
- low insertion loss
- latch for connector locking
- pre-polished ceramic ferrule, 1,25 mm
- with kink protection sleeves
- life > 1000 cycles
- 5 m

Features

General	
Design	plug, ceramic sleeve
Classification	OS2 APC (8€)
Halogen Free	Yes
Country of manufacture	CN
GTIN (EAN)	4043921665046
Dimensions/Weights without packaging	
Cable length mm	5.000
Cable diameter mm	3
Cable construction	9/125µm, Grade C1
Net weight piece kg	0,033
Certifications	
RoHS conform	Yes
Logistics Information	
Packaging	polybag
Packaging unit Quantity	1
Packaging unit Weight kg	0,039
Packaging unit Width mm	180
Packaging unit Height mm	210
Packaging unit Depth mm	20
References	
Accessories	228030006, 228030012, 228030024, 228030106, 228030112, 228030124, 228030206, 228030212, 228030224, 228030306, 228030312, 228030324, 228030406, 228030412, 228030424
Similar article	228050005, 228050105, 228050205, 228050305, 228050402