




Matching SLIM series pendant lamps are available for the current track system. The light body in die-cast aluminium is always the same size (300 x 39 mm). The pendant lamps for current tracks allow suspended mounting up to max. 180 cm.

The single-luminaire SLIM current track light therefore is especially well suited to gastronomy and retail projects with variable room layouts. The value of the Slim series is rounded off with a flexible fabric cable.



#### Special features

- Die-cast aluminium
- Fabric cable
- Particularly glare-free thanks to low UGR value
- Suspended mounting up to 1800 mm

<b>Housing Material</b>	Aluminium	<b>Pendulum Length max.</b>	1500 mm
<b>Housing Color</b>	Black	<b>Product weight</b>	476 g
<b>Colour of Lens</b>	Transparent	<b>Working Temperature</b>	-20 to 45 °C
<b>Surface Structure of Lens</b>	Structured	<b>Storage Temperature</b>	-20 to 65 °C
<b>Protection Class</b>	Protection class I/protective grounding	<b>IP Protection Class</b>	IP 20
<b>Rated Input</b>	5 W	<b>Life Time L70 / B50</b>	50000 h
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz	<b>Switching Cycles</b>	100000
<b>Power Supply Unit incl.</b>	Yes	<b>Power Consumption</b>	5 kWh/1000h
<b>Connection Type</b>	Adapter	<b>Energy Efficiency Class Lightsource</b>	This product contains a light source of energy efficiency class E.
<b>Dimmable</b>	Yes		
<b>Control technology</b>	Leading-edge dimmer, Trailing-edge dimmer		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source changeable TC		
<b>Lightcolor</b>	Warm white (WW)		
<b>Color Temperature</b>	2700 K		
<b>Colour Consistency</b>	3 SDCM		
<b>Colour Rendering Index (Ra)</b>	90		
<b>Rated Luminous Flux</b>	500 lm		
<b>Luminous Efficiency</b>	100 lm/W		
<b>Rated Angle of Reflection</b>	24 Degree		
<b>UGR</b>	19		
<b>Light Distribution</b>	Symmetric		
<b>Distribution Characteristic 120°</b>	DLS		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Below		
<b>Length</b>	1800 mm		
<b>Height</b>	300 mm		
<b>Diameter</b>	39 mm		