## lightnet

## Ringo Star-G3

Pendant luminaire - Direct light distribution





Article code: RG3OBE-840M-D1200-U

Illustrations may only be similar and serve as an orientation.

Ringo Star-G3. LED. Pendant luminaire. Luminaire body made of aluminium profile with 60mm track width. Surface finish Jet Black. Direct only light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. Switchable. DxHxW (round). D=1200mm. W= 60mm. H=85mm. Central cord suspension with ceiling rose and power supply cable (Set). Pendant length max 4000mm. Power supply: transparent.


Ceiling rose: Matching luminaire's surface colour. Medium-power current. 6600lm. 81W. 11,2kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.

## lightnet

## Ringo Star-G3

Pendant luminaire - Direct light distribution







Article code: RG3OBE-840M-D1200-U

Customer / Proj	ject:		
Note:			

Productname Ringo Star-G3

LED Lamp

Installation Type Pendant luminaire

Surface finish Jet Black

Light characteristics Direct light distribution

4000K Colour temperature Colour Rendering Index (CRI) CRI>80 Optical system Opal diffuser Control Switchable Length L/Diameter D (mm) D=1200mm Width W (mm) W=60mm Height H (mm) H=85mm Current/Power Medium-Power

6600lm Luminous Flux Power consumption 81W

Suspension Central susp. (Set)

Ceiling rose colour Ceiling rose: Matching luminaire`s

surface colour

Pendant length (mm) Pendant length max 4000mm

Degree of protection

Cable Colour Power supply: transparent LED lifetime L85B10 (tq  $25^{\circ}$ C) = 50.000h

Photometric code 8 40 / 3 3 9 Photobiological class RG0 (EN62471)

Indoor/Outdoor Indoor: ta [ambient] max. 25°C

Weight (kg) 11,2kg





















