



LUCEA series pendant lamps are available in 10, 15 and 20 W versions and offer up to 2,000 lumens light output. The maximum suspended mounting is 1,800 mm. Using optional lenses, the light emission angle of the individual models can be narrowed or expanded. Lucea lights feature a die-cast aluminium housing

Special features

- High colour rendering
- Light colour adjustable in 2 stages
- Housing made from die-cast aluminium
- Max. suspended mounting 1,800 mm
- Dimmable

Housing Material	Aluminium	Life Time L70 / B50	50000 h
Housing Color	White	Switching Cycles	100000
Material of Lens	PMMA	Power Consumption	6 kWh/1000h
Protection Class	Protection class I/protective grounding	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class E.
Rated Input	6 W		
Rated Input Voltage Frequency	200-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Dimmable	Yes		
Control technology	Leading-edge dimmer, Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	2700 K		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	800 lm		
Rated Angle of Reflection	36 Degree		
Light Distribution	Symmetric		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Height	157 mm		
Diameter	65 mm		
Base height	29 mm		
Base diameter	104.5 mm		
Pendulum Length max.	1800 mm		
Working Temperature	-20 to 40 °C		
Storage Temperature	-20 to 65 °C		
IP Protection Class	IP 20		