

## BASIC MAX G1/P1 | SUSPENDED TUBE SUSPENSION (D400 - D600)

### 1. MONTAGE UND INSTALLATION | MOUNTING AND INSTALLATION:

D400 - D600  
 TUBE: Ø13

1. Bei allen Montagearbeiten Handschuhe tragen.  
 Use gloves when handling the fixture.

2. Montageöffnungen.  
 Installation openings.

3.

4.

5.

- min/max stripped wire length: 7mm-10mm

- max power supply cable: 1,5mm<sup>2</sup>

6.

7.

8.

Diffuser direction

INSIDE  
 gloss

prism matt

OUTSIDE

9.

## BASIC MAX G1/P1 | SUSPENDED TUBE SUSPENSION (D900)

### 1. MONTAGE UND INSTALLATION | MOUNTING AND INSTALLATION:

D900  
 TUBE: Ø35

1. Bei allen Montagearbeiten Handschuhe tragen.  
 Use gloves when handling the fixture.

2. Montageöffnungen.  
 Installation openings.

3.

4.

5.

- min/max stripped wire length: 7mm-10mm

- max power supply cable: 1,5mm<sup>2</sup>

6.

Diffuser direction

INSIDE  
 gloss

prism matt

OUTSIDE

7.