

Han Gigabit insert male



Part number	09 14 008 3011
Specification	Han Gigabit insert male
HARTING eCatalogue	https://b2b.harting.com/09140083011

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Inserts
Specification	Han [®] Gigabit insert
Features	Suitable for PoE++

Version

Termination method	Crimp termination
Gender	Male
Number of contacts	8
further contacts	+ shielding
Details	Please order crimp contacts separately.
	Please order adapter module separately.
	Please order cable clamp or crimp flange separately.

Technical characteristics

Conductor cross-section	0.09 0.52 mm²
Rated current	5 A
Rated voltage	50 V
Rated voltage	50 V AC 60 V DC
Rated impulse voltage	0.8 kV
Pollution degree	3
Rated voltage acc. to UL	30 V
Transmission characteristics	Cat. 6 _A Class E _A up to 500 MHz

Page 1 / 3 | Creation date 2022-09-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Technical characteristics

Data rate	10 Mbit/s 100 Mbit/s 1 Gbit/s 2.5 Gbit/s 5 Gbit/s 10 Gbit/s
Contact resistance, shielding	≤100 mΩ
Limiting temperature	-40 +85 °C
Mating cycles	≥500
Material properties	
Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material (shielding)	Zinc die-cast, nickel-plated
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained

Fire protection on railway vehiclesEN 45545-2 (2020-08)Requirement set with Hazard LevelsR22 (HL 1-3)R23 (HL 1-3)

Not contained

Not contained

Yes

Specifications and approvals

California Proposition 65 substances

REACH ANNEX XIV substances

REACH SVHC substances

REACH SVHC substances

ECHA SCIP number

Specifications	IEC 60664-1 IEC 61984
Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076

Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate

1e38d35d-d1be-4585-8e03-95faccd739bf

Commercial data

Packaging size

1

Page 2 / 3 | Creation date 2022-09-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com Product data sheet 09 14 008 3011 Han Gigabit insert male



Commercial data

Net weight	36.55 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140020658
eCl@ss	27440218 Module for industrial connectors (data)

Page 3 / 3 | Creation date 2022-09-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com