

**Special features**

- Light colour adjustable in 3 stages
- Low glare value
- Low housing depth
- Optionally available as pendant lamp

Housing Material	Aluminium	Working Temperature	-20 to 45 °C
Housing Color	White	Storage Temperature	-40 to 80 °C
Material of Lens	PMMA	IP Protection Class	IP 40
		IK Protection Class	IK03
Protection Class	Protection class III/safety extra-low voltage	Life Time L70 / B50	40000 h
Operating Mode	Constant current	Switching Cycles	100000
Rated Input	51.5 W	Power Consumption	52 kWh/1000h
Rated Input Voltage	33-38 V/DC	Energy Efficiency Class	F
Rated Current	1500 mA		
Power Supply Unit incl.	No		
Secondary Connection	Open cables		
Dimmable	Yes		
Control technology	Dimmable via optional power supply unit		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000/4000/6000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	5300/6000/5700 lm		
Rated Luminous Flux 2	6000 lm		
Luminous Efficiency	110.7 lm/W		
Rated Angle of Reflection	120 Degree		
UGR	22		
Distribution Characteristic 120°	NDLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Length	1240 mm		
Width	620 mm		
Height	9 mm		