

Docking Frame for 4 modules, float mount




Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 14 016 1701 |
| Specification | Docking Frame for 4 modules, float mount |
| HARTING eCatalogue | https://b2b.harting.com/09140161701 |

Identification

| | |
|------------------------------|---|
| Category | Accessories |
| Series | Han-Modular® |
| Type of accessory | Docking frame |
| Description of the accessory | Float mount for 4 modules A ... D |

Technical characteristics

| | |
|---|-----------------|
| Limiting temperature | -40 ... +125 °C |
| Mating cycles | ≥500 |
| Mating cycles with other HMC components | ≥10,000 |
| Degree of protection acc. to IEC 60529 | IP20 |
| Floating tolerance | ±2 mm |
| Lock-in range | ±4 mm |

Material properties

| | |
|---|--------------------|
| Material | Polycarbonate (PC) |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |



Pushing Performance
Since 1945

Material properties

| | |
|-------------------------------------|------------------------------|
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R22 (HL 1-3) R23 (HL 1-3) |

Specifications and approvals

| | |
|----------------|--------------------------|
| Specifications | IEC 60664-1 IEC 61984 |
|----------------|--------------------------|

Commercial data

| | |
|--------------------------------|---|
| Packaging size | 2 |
| Net weight | 25 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| GTIN | 5713140021112 |
| eCl@ss | 27440206 Module carrier frame for industrial connectors |