



Special features

- Base L x W x H: 102 x 102 x 7 mm
- Movement/twilight sensor

Housing Material	Die-cast aluminium
Housing Color	Grey
Material of Lens	Plastic
Colour of Lens	White

Working Temperature	-20 to 50 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 44

Protection Class	Protection class I/protective grounding
Rated Input	6.5 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	No
Motion Detector	Yes
Kind of Motion Detector	Infrared
Detection Distance	1-10 m
Angle of Detection	90 Degree

Life Time L70 / B50	30000 h
Switching Cycles	20000
Power Consumption	7 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	290 lm
Rated Angle of Reflection	120 Degree
Distribution Characteristic 120°	NDLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Side

Length	70 mm
Width	70 mm
Height	800 mm
Base length	102 mm
Base width	102 mm
Base height	7 mm