

## DIN-Signal coax f, pcb-solder, 75Ohm




Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 09 03 000 6269  |
| Specification      | DIN-Signal coax f, pcb-solder, 75Ohm  |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09030006269">https://b2b.harting.com/09030006269</a> |

### Identification

|                            |  |
|----------------------------|--|
| Category                   | Contacts   |
| Series                     | DIN 41612  |
| Type of contact            | Coaxial contact  |
| Description of the contact | Angled   |
| Contacts for               | DIN 41612 Type M<br>DIN 41612 Type MH 21+5<br>DIN 41612 Bauform M 0+2<br>har-modular <sup>®</sup> M module, male, angled |

### Version

|                       |                                    |
|-----------------------|------------------------------------|
| Termination method    | PCB solder termination             |
| Gender                | Female contact for male connectors |
| Manufacturing process | Turned contacts                    |

### Technical characteristics

|                       |   |
|-----------------------|---|
| Operating current     | ≤1.5 A  |
| Rated voltage         | 250 V   |
| Insulation resistance | >10 <sup>9</sup> Ω                                      |
| Contact resistance    | ≤10 mΩ for inner contact die<br>≤3 mΩ for outer ferrule |
| Impedance             | 75 Ω  |
| Limiting temperature  | -55 ... +125 °C   |
| Return loss           | >37 dB @ 1 GHz<br>>27 dB @ 2 GHz                        |



Pushing Performance  
Since 1945

## Technical characteristics

|                           |         |
|---------------------------|---------|
| Insertion force           | ≤10 N   |
| Withdrawal force          | ≥1 N    |
| Performance level         | 1       |
| Mating cycles             | ≥500    |
| Test voltage $U_{r.m.s.}$ | 0.75 kV |
| Frequency                 | 2 GHz   |

## Material properties

|                                      |  |
|--------------------------------------|--|
| Material (contacts)                  | Copper alloy   |
| Surface (contacts)                   | Noble metal over Ni Mating side                        |
| Material (locking)                   | Copper alloy   |
| RoHS                                 | compliant with exemption                               |
| RoHS exemptions                      | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status                           | compliant with exemption                               |
| China RoHS                           | 50   |
| REACH Annex XVII substances          | Not contained  |
| REACH ANNEX XIV substances           | Not contained  |
| REACH SVHC substances                | Yes  |
| REACH SVHC substances                | Lead   |
| ECHA SCIP number                     | 339476a1-86ba-49e9-ab4b-cd336420d72a                   |
| California Proposition 65 substances | Yes  |
| California Proposition 65 substances | Lead<br>Nickel   |

## Specifications and approvals

|                |           |
|----------------|-----------|
| Specifications | DIN 41626 |
|----------------|-----------|

## Commercial data

|                                |               |
|--------------------------------|---------------|
| Packaging size                 | 30            |
| Net weight                     | 0.1 g         |
| Country of origin              | Germany       |
| European customs tariff number | 85366990      |
| GTIN                           | 5713140004184 |



**Pushing Performance**  
Since 1945

## Commercial data

eCl@ss

27440204 Contact for industrial connectors

---