

## HARTING M12 housing male front mounting



Image is for illustration purposes only. Please refer to product description.

Part number	21 03 301 1003
Specification	HARTING M12 housing male front mounting
HARTING eCatalogue	<a href="https://b2b.harting.com/21033011003">https://b2b.harting.com/21033011003</a>

### Identification

Category	Accessories
Series	Circular connectors M12
Identification	PushPull
Type of accessory	Housing
Description of the accessory	for front mounting

### Version

Gender	Male
Locking type	Screw locking

### Technical characteristics

Tightening torque	2 Nm Lock nut
Degree of protection acc. to IEC 60529	IP65 / IP67 mated condition

### Material properties

RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes



Pushing Performance  
Since 1945

## Material properties

REACH SVHC substances	6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol Lead
ECHA SCIP number	0d7d3693-d625-47ab-934a-d241bf72c86e
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R26

## Specifications and approvals

Specifications	IEC 61076-2-010
----------------	-----------------

## Commercial data

Packaging size	10
Net weight	18.73 g
Country of origin	Romania
European customs tariff number	85389099
GTIN	5713140236356
eCl@ss	27440292 Connector component (accessories)