

**Special features**

- Including 1.2 m connecting cable with IP44 shaped plug

| | | | |
|----------------------------------------------|-----------------------------------------|---------------------------------|--------------|
| Housing Material | Die-cast aluminium | Storage Temperature | -10 to 60 °C |
| Housing Color | Silver | IP Protection Class Lamp | IP 65 |
| Material of Lens | Glass | IP Protection Class Plug | IP 44 |
| | | IK Protection Class | IK08 |
| Protection Class | Protection class I/protective grounding | | |
| Rated Input | 30 W | Life Time L70 / B50 | 30000 h |
| Rated Input Voltage | 220-240 V/AC 50 / 60 Hz | Switching Cycles | 150000 |
| Frequency | | Power Consumption | 30 kWh/1000h |
| Power Supply Unit incl. | Yes | Energy Efficiency Class | E |
| Connection Cable Primary | Yes | | |
| Primary Connection | Power plug IP44 | | |
| Primary Cable Length | 1.2 m | | |
| Connection Type According to Standard | Typ Y | | |
| Dimmable | No | | |
| Motion Detector | No | | |
| Light Source | LED, Light source not changeable | | |
| Color Temperature | 3000 K | | |
| Colour Consistency | 5 SDCM | | |
| Colour Rendering Index (Ra) | 80 | | |
| Rated Luminous Flux | 3600 lm | | |
| Rated Angle of Reflection | 100 Degree | | |
| UGR | 25 | | |
| Distribution Characteristic 120° | DLS | | |
| Light Exit Surfaces | 1 | | |
| Light characteristics | Direct | | |
| Light direction | Below | | |
| Length | 237 mm | | |
| Width | 250 mm | | |
| Height | 40.5 mm | | |
| Working Temperature | -20 to 40 °C | | |