

Connector - with screwless terminals, lockable



Product description	
BALS-Prd.-Nr	310635
EAN	4024941197540
product category (PG)	Connector QUICK-CONNECT
current (A)	32A
number of poles (P99)	5p
number of poles (P)	3p+N+PE
position of earth contact (H)	6 h
voltage (V)	200/346 up to 240/415V
frequency (HZ)	50 and 60Hz

Product description	
protection degree (SA)	IP44
colour code 1 (KF1)	red RAL 3000
Colour of appliance	Housing cover red RAL 3000, Collar red RAL 3000, Hinged lid red RAL 3000, Cable gland grey RAL 7035
connection design (AT)	screwless spring-clamp technology
maximum conductor size (LQ)	6,0 qmm
cable entry (KE)	Cable gland
Height	188mm
Width	92mm
Depth	102mm
material of enclosure (GM)	Polyamide
contact	The contact carrier is made of polyamide, the contacts are brass nickel plated

Additional technical properties	
	Multi-Grip cable gland with gasket and integrated strain relief, Screwless housing connection with snap fastening, The connector is lockable with the plug art.-no. 210951 and padlock art.no. 580642, For cable diameter from 11 up to max. 23,5 mm

Logistics data	
Weight/pcs	0.297 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941197540
Length	102 mm
Width	92 mm
Height	188 mm
Weight	0.298 kg
Volume	1,764.192 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941825665
Length	325 mm
Width	217 mm
Height	210 mm
Weight	3.176 kg
Volume	13,588.4 ccm

