



A modern standing lamp for office rooms with modern control technology. The minimalistic light automatically switches on if there is movement. In addition, the OFFICE THREE MOTION adapts to the daylight conditions present and regulates the brightness for relaxed working even over longer periods of time. Movement sensor and daylight sensor can be deactivated separately from each other. The direct and indirect light proportion can be controlled separately. Thanks to UGR < 6, the light is particularly glare-free and ideal for lighting up individual work spaces.

#### Special features

- Particularly low glare value
- Daylight and movement sensor
- Dimmable using touch panel
- High lumen output
- Direct and indirect light

<b>Housing Material</b>	Aluminium	<b>Light direction</b>	Top, Below
<b>Housing Color</b>	Aluminum	<b>Length</b>	1056 mm
<b>Material of Lens</b>	Plastic	<b>Width</b>	64 mm
<b>Protection Class</b>	Protection class I/protective grounding	<b>Height</b>	1950 mm
<b>Power Selectable</b>	55 W, 25 W	<b>Base length</b>	500 mm
<b>Rated Input Voltage</b>	200-240 V/AC 50 / 60 Hz	<b>Base width</b>	225 mm
<b>Frequency</b>		<b>Product weight</b>	11310 g
<b>Power Supply Unit incl.</b>	No	<b>Working Temperature</b>	-20 to 45 °C
<b>Connection Cable Primary</b>	Yes	<b>Storage Temperature</b>	-40 to 80 °C
<b>Primary Connection</b>	Power plug	<b>IP Protection Class</b>	IP 20
<b>Primary Cable Length</b>	2.5 m	<b>Life Time L70 / B50</b>	50000 h
<b>Connection Type According to Standard</b>	Typ Y	<b>Life Time L80 / B10</b>	50000 h
<b>Dimmable</b>	Yes	<b>Switching Cycles</b>	25000
<b>Control technology</b>	Touch-Sensor	<b>Power Consumption</b>	80 kWh/1000h
<b>Motion Detector</b>	Yes	<b>Energy Efficiency Class</b>	D
<b>Kind of Motion Detector</b>	Infrared		
<b>Detection Distance</b>	0-3.5 m		
<b>Angle of Detection</b>	85 Degree		
<b>Light Source</b>	LED, Light source not changeable		
<b>Lightcolor</b>	Neutral white		
<b>Color Temperature</b>	4000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	9600 lm		
<b>Luminous Efficiency</b>	120 lm/W		
<b>Rated Angle of Reflection</b>	110 Degree		
<b>Rated Angle of Reflection 2</b>	50 Degree		
<b>UGR</b>	6		
<b>Distribution Characteristic 120°</b>	DLS		
<b>Light Exit Surfaces</b>	2		
<b>Light characteristics</b>	Direct		

