



Little helper, big effect. With the HERCULIS display lights in a high-quality aluminium housing, you can reach all corners of a display case. To do so, the lamp head with its 40° light emission angle can be freely rotated and swivelled in any direction. In addition, the intelligent cable routing and the ready-to-use system enable easy surface and recessed mounting in display cases, counters, sales areas or in living rooms.

Special features

- High output with compact design
- Rotatable and swivelling heads
- For panel and surface mounting
- Intelligent cable routing
- Ready-to-use system

Housing Material Die-cast aluminium
Housing Color Black

Protection Class Protection class III/safety extra-low voltage

Operating Mode Constant current

Rated Input 1 W

Rated Input Voltage 3 V/DC

Rated Current 350 mA

Power Supply Unit incl. No

Connection Cable Secondary Yes

Secondary Connection Plug mini AMP

Secondary Cable Length 1 m

Dimmable No

Motion Detector No

Light Source LED, Light source not changeable

Color Temperature 4000 K

Colour Consistency 6 SDCM

Colour Rendering Index (Ra) 90

Rated Luminous Flux 105 lm

Rated Angle of Reflection 40 Degree

Distribution Characteristic 120° DLS

Swivel Angle 180 Degree

Light Exit Surfaces 1

Light characteristics Direct

Light direction Top

Height 42.2 mm

Diameter 31 mm

Base height 5 mm

Base diameter 31 mm

Working Temperature -10 to 45 °C

Storage Temperature -10 to 45 °C

IP Protection Class IP 20

Life Time L70 / B50 30000 h

Switching Cycles 50000

Power Consumption 1 kWh/1000h

Energy Efficiency Class G