



Whilst flat surfaces and covers are the go-to for most surface-mounted ceiling lights, the ZANIAH places special emphasis on its 360° lamp [either a 12W, 18W or 21W variant]. This isn't just for visual reasons, as the ZANIAH can be combined with covers from the similarly new ORBIT series if needed. This means that not only are different colours available - the ZANIAH itself comes in eight colour variants per performance class.

**Special features**

- 360° light emission angle
- Dimmable

<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	Red
<b>Material of Lens</b>	Plastic
<b>Protection Class</b>	Protection class II/protective insulation
<b>Rated Input</b>	12 W
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz
<b>Power Supply Unit incl.</b>	Yes
<b>Connection Type</b>	Clamp
<b>Dimmable</b>	Yes
<b>Control technology</b>	Leading-edge dimmer, Trailing-edge dimmer
<b>Motion Detector</b>	No
<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	3000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	1510 lm
<b>Rated Angle of Reflection</b>	120 Degree
<b>Distribution Characteristic 120°</b>	NDLS
<b>Light Exit Surfaces</b>	2
<b>Light characteristics</b>	Direct, Indirect
<b>Light direction</b>	Below, Rear
<b>Height</b>	42 mm
<b>Diameter</b>	290 mm
<b>Working Temperature</b>	-20 to 45 °C
<b>Storage Temperature</b>	-10 to 60 °C
<b>IP Protection Class</b>	IP 20
<b>IK Protection Class</b>	IK05
<b>Life Time L70 / B50</b>	50000 h

<b>Switching Cycles</b>	25000
<b>Power Consumption</b>	12 kWh/1000h
<b>Energy Efficiency Class</b>	F