


RGB radio control
Artikel-Nr. 18233000



RGB radio control, RGB radio controller for controlling the RGB LED modules in the color light range. Controller: voltage: 12-24 V DC, current: maximum 3 x 3.33 A. Power: maximum 180 W / 360 W (12 V DC / 24 V DC). Control: negative (common anode). Control signal: PWM. Radio frequency: 869.5 MHz,. Range (visual contact): up to 20 m. Ambient temperature (ta): 0 °C to +40 °C. Controller connection using screw terminals. Dimensions: L 178 x W 46 x H 18 mm. Material: Plastic. Delivery: including strain relief. Controller per remote control: maximum 4 (for optimum radio connection). Remote control: Voltage (battery): 4.5 V DC - 3 x AAA (not included in the scope of delivery). Radio frequency: 869.5 MHz. Transmission power (Ps) < 0 dBm. Range (visual contact): up to 20 m. Ambient temperature (ta): 0 °C to +40 °C. Dimensions: L 120 x W 48 x H 18 mm. Material: Plastic. Function scope: On / Off. RGB color change using a touch wheel. Dimmer keys for red / green / blue. Color gradient: Start / Stop. Color gradient: Speed. Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Voltage: 12V 24V, Power: 240W, control: Wireless technology control.

Artikel-Nr.	18233000
Stand:	06.12.2021 18:30

Description	RGB-Set (Controller inkl. Fernbedienung)
Material	Plastic
Control	Wireless technology control
Degree of protection	IP20

Protection class	III
Voltage	12V 24V
Environment temperature (ta)	0 °C bis +40 °C
Circuit type	Parallel conduction