



Product Features

- metal housing
- for use in 10 Gigabit-Ethernet-Networks (transmission bandwidth 500 MHz)
- 2 x RJ45, shielded
- angular coupling (90°)
- for standard keystone cutouts (14,7 x 19,3mm)
- metal housing
- suitable für PoE (Power over Ethernet) according to IEEE 802.3af
- according to the following standards
- ISO/IEC 11 801, ClassEA, shielded
- DIN EN 50173-1, ClassEA, shielded
- DIN EN 60 603-7-51, 500 MHz, shielded
- life > 750 cycles

Features

General	
Surface	zinc die-cast, refined
Design	jack/jack
shielded	Yes
Classification	ClassEA iso
PoweroverEthernet	Yes
Protection class IP	21
Halogen Free	Yes
Country of manufacture	TW
GTIN (EAN)	4043921663172
Mounting types	
keystone-adapter	Yes
Dimensions/Weights without packaging	
Length mm	15
Width mm	22
Height mm	36
Net weight piece kg	0,01
Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes

Logistics Information	
Packaging	box
Packaging unit Quantity	10
Packaging unit Weight kg	0,12
Packaging unit Width mm	120
Packaging unit Height mm	75
Packaging unit Depth mm	15
References	
Accessories	13900001, 13900002, 13900005, 13911501, 17000030, 17000055, 17000065, 23900000, 23910106, 23910108, 23910112, 23910116, 23910118
Similar article	13900330, 13900360

