



Flexible waymarker - The Antilae LED path light provides bordering, path marking and visual elegance in gardens, on patios or in car parks. With its 80-cm-high housing made from dark grey die-cast aluminium with IP65 degree of protection, the Antilae is a robust and resilient functional lighting product providing a warm white ambience (3,000 K).

**Special features**

- Base L x W x H: 152 x 121 x 20 mm

<b>Housing Material</b>	Die-cast aluminium	<b>Life Time L70 / B50</b>	25000 h
<b>Housing Color</b>	Grey	<b>Switching Cycles</b>	15000
<b>Material of Lens</b>	Plastic	<b>Power Consumption</b>	13 kWh/1000h
<b>Protection Class</b>	Protection class I/protective grounding	<b>Energy Efficiency Class</b>	G
<b>Rated Input</b>	13 W		
<b>Rated Input Voltage Frequency</b>	100-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Cable Primary</b>	Yes		
<b>Primary Connection</b>	Connection box		
<b>Dimmable</b>	No		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Color Temperature</b>	3000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	650 lm		
<b>Distribution Characteristic 120°</b>	NDLS		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Indirect		
<b>Light direction</b>	Below		
<b>Length</b>	152 mm		
<b>Width</b>	121 mm		
<b>Height</b>	800 mm		
<b>Base length</b>	152 mm		
<b>Base width</b>	121 mm		
<b>Base height</b>	20 mm		
<b>Working Temperature</b>	-20 to 40 °C		
<b>Storage Temperature</b>	-10 to 60 °C		
<b>IP Protection Class</b>	IP 65		