

Wall mounting socket outlet - straight, housing dimensions 102x102 mm





| Product description | |
|---------------------------|--|
| BALS-Prd.-Nr | 110570 |
| EAN | 4024941938679 |
| Product category | TE wall mounting socket outlet Quick-Connect |
| Current | 32A |
| Number of poles | 3p |
| Poles | 2P+PE |
| Position of earth contact | 9 h |
| Voltage | 380 up to 415V |

| Product description | |
|------------------------|--|
| Frequency | 50 and 60Hz |
| Protection degree | IP67 |
| Colour code | red RAL 3000 |
| Colour of appliance | Hinged lid red RAL 3000, Enclosure grey RAL 7035 |
| Connection design | screwless spring-clamp Kontex |
| Maximum conductor size | 10,0 qmm |
| Cable entry | 3 sides 2x M20/25, 1 side 1x M20/25, to break out |
| Height | 102mm |
| Width | 102mm |
| Depth | 134mm |
| Dimension of enclosure | 102x102 mm (HxW) |
| Material of enclosure | Polyamide |
| Contact | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical properties | |
|---------------------------------|------------------------------------|
| | All cable entries are to break out |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.415 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |

| Logistics data | |
|----------------|---------------|
| EAN | 4024941938679 |
| Length | 134 mm |
| Width | 102 mm |
| Height | 102 mm |
| Weight | 0.416 kg |
| Volume | 1,394.136 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941828499 |
| Length | 330 mm |
| Width | 216 mm |
| Height | 260 mm |
| Weight | 4.376 kg |
| Volume | 17,062.5 ccm |



| Ampere Polzahl | 16 3 | 16 4 | 16 5 | 32 3 | 32 4 | 32 5 |
|----------------------------|----------|----------|----------|----------|----------|----------|
| a | 102,0 | 102,0 | 102,0 | 102,0 | 102,0 | 102,0 |
| b | 102,0 | 102,0 | 102,0 | 102,0 | 102,0 | 102,0 |
| c | 88,0 | 88,0 | 88,0 | 88,0 | 88,0 | 88,0 |
| d | 88,0 | 88,0 | 88,0 | 88,0 | 88,0 | 88,0 |
| e | 68,0 | 68,0 | 68,0 | 68,0 | 68,0 | 68,0 |
| f | 124,0 | 125,0 | 124,0 | 134,0 | 134,0 | 134,0 |
| g | 4,0 | 4,0 | 4,0 | 4,0 | 4,0 | 4,0 |
| h ø | 4,5 | 4,5 | 4,5 | 4,5 | 4,5 | 4,5 |
| i | 2xM20/25 | 2xM20/25 | 2xM20/25 | 2xM20/25 | 2xM20/25 | 2xM20/25 |
| k | M20/25 | M20/25 | M20/25 | M20/25 | M20/25 | M20/25 |
| Leiter mm ² min | 1,5 | 1,5 | 1,5 | 2,5 | 2,5 | 2,5 |
| Leiter mm ² max | 4 | 4 | 4 | 10 | 10 | 10 |

1 MB 121