

lightnet

Cubic-X2

Surface mounted luminaire - Direct/indirect light distribution

Article code: CX2OEE-830M-Q430



Illustrations may only be similar and serve as an orientation.





Cubic-X2. LED. Wall or ceiling mounted luminaire. Luminaire body with distance-spacer. Luminaire body made of high-quality aluminum profile. Surface finish Silver Anodised. Direct light distribution and indirect lighting corona. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. Switchable. LxWxH (square). L= 430mm. W=430mm. H=75mm.

Medium-power current. 4142lm. 30W. 5,1kg. Binning initial \leq MacAdam 3. IP20. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.

Cubic-X2

Surface mounted luminaire - Direct/indirect light distribution

Article code: CX2OEE-830M-Q430



Customer / Project: _____

Note: _____

Productname	Cubic-X2
Lamp	LED
Installation Type	Surface mounted luminaire
Surface finish	Silver Anodised
Light characteristics	Direct/indirect light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Opal diffuser
Control	Switchable
Length L/Diameter D (mm)	L=430mm
Width W (mm)	W=430mm
Height H (mm)	H=75mm
Current/Power	Medium-Power
Luminous Flux	4142lm
Power consumption	30W
Degree of protection	IP20
Certification	Prüfzeichen: ENEC
LED lifetime	L85B10 (tq 25°C) = 50.000h
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	5,1kg

