



SCULPTORIS series pendant lamps boast an impressive matte visual design and luminous ring. With high luminous intensity and large light emission angle, the series offers flexible applications in many different areas, whether in living areas or for providing imposing lighting solutions to office spaces.

Special features

- Light colour adjustable in 2 stages
- Uniform illumination
- Circumferential diffuser
- Suspended mounting up to 1,800 mm

Housing Material	Aluminium
Housing Color	Black
Housing Surface	Matt
Material of Lens	Acryl
Surface Structure of Lens	Satined
Protection Class	Protection class I/protective grounding
Rated Input	60 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	Yes
Control technology	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No

Working Temperature	-10 to 45 °C
Storage Temperature	-10 to 45 °C
IP Protection Class	IP 20

Life Time L70 / B50	30000 h
Switching Cycles	20000
Power Consumption	60 kWh/1000h
Energy Efficiency Class Lightsources	This product contains a light source of energy efficiency class F.

Light Source	LED, Light source changeable TC
Color Temperature	3000/4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	4100/4200 lm
Rated Luminous Flux 2	4200 lm
Rated Angle of Reflection	150 Degree
Light Distribution	Symmetric
Light Exit Surfaces	1
Light characteristics	Direct, Indirect
Light direction	Top, Below
Height	110 mm
Diameter	800 mm
Base height	65 mm
Base diameter	275 mm
Pendulum Length max.	3000 mm