



- Can be dimmed using Dali1/Dali2
- Can be dimmed using 230 V push button [on/off, brightness]
- Intelli-Push function [shortcut synchronises all connected power supply units when needed]
- Current range adjustable using DIP switch
- Can be operated without actuation/dimming
- Dimming range 1-100 %
- Flicker-free
- Short circuit and overload protection
- Safe against overheating

**Special features**

- Can be dimmed using Dali1/Dali2
- Can be dimmed using 230 V push button [on/off, brightness]
- Intelli-Push function [shortcut synchronises all connected power supply units when needed]
- Current range adjustable using DIP switch
- Can be operated without actuation/dimming
- Dimming range 1-100 %
- Flicker-free
- Short circuit/overload protection, overheating protection

<b>Housing Material</b>	Plastic
<b>Housing Color</b>	Black
<b>Operating Mode</b>	Constant current
<b>Protection Class</b>	Protection class II/protective insulation
<b>Power</b>	3.2-12 W
<b>Output Voltage</b>	15-52 V/DC
<b>Output Current Selectable</b>	180 mA, 230 mA, 260 mA, 300 mA, 350 mA, 400 mA, 450 mA, 500 mA
<b>Dimmable</b>	Yes
<b>Control</b>	DALI 2 / DT6, Intelli Push-Dim
<b>Number of Channels</b>	1
<b>Power Factor</b>	0.95
<b>Connection Type</b>	Clamp

<b>Number of Circuit Breaker B10A max.</b>	23
<b>Number of Circuit Breaker B16A max.</b>	37
<b>Number of Circuit Breaker C10A max.</b>	46
<b>Number of Circuit Breaker C16A max.</b>	74
<b>Inrush Current max.</b>	30 A / 100 μs
<b>Capacitive Load</b>	195.42 nF
<b>Reference Point Tc</b>	80 °C
<b>Working Temperature</b>	-20 to 50 °C
<b>Storage Temperature</b>	-20 to 70 °C
<b>IP Protection Class</b>	IP 20

<b>Length</b>	119 mm
<b>Width</b>	52 mm
<b>Height</b>	24 mm
<b>Product weight</b>	99 g

Multi-CC variable power/voltage ranges		
Current	Power	Voltage
180mA	3,20W - 9,80W	18V - 54V
230mA	4,00W - 12,00W	18V - 52V
260mA	4,00W - 12,00W	15V - 46V
300mA	4,50W - 12,00W	15V - 42V
350mA	5,20W - 12,00W	15V - 34V
400mA	6,00W - 12,00W	15V - 30V
450mA	6,80W - 12,00W	15V - 27V
500mA	7,50W - 12,00W	15V - 24V
max. 2 lamps per channel - check voltage range!		

