



A modern standing lamp for office rooms with modern control technology. The minimalistic light automatically switches on if there is movement. In addition, the OFFICE THREE MOTION adapts to the daylight conditions present and regulates the brightness for relaxed working even over longer periods of time. Movement sensor and daylight sensor can be deactivated separately from each other. The direct and indirect light proportion can be controlled separately. Thanks to UGR <math>< 6</math>, the light is particularly glare-free and ideal for lighting up individual work spaces.

Special features

- Particularly low glare value
- Daylight and movement sensor
- Dimmable using touch panel
- High lumen output
- Direct and indirect light

Housing Material	Aluminium
Housing Color	Black
Housing Surface	Matt
Material of Lens	Plastic
Protection Class	Protection class I/protective grounding
Power Selectable	55 W, 25 W
Rated Input Voltage Frequency	200-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Cable Primary	Yes
Primary Connection	Power plug
Primary Cable Length	2.5 m
Dimmable	Yes
Control technology	Touch-Sensor
Motion Detector	Yes
Kind of Motion Detector	Infrared
Detection Distance	0-3.5 m
Angle of Detection	85 Degree

Light Source	LED, Light source not changeable
Lightcolor	Warm white/neutral white/cold white
Colour Temperature	3000-5700 K
Colour Consistency	3 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	8700 lm
Luminous Efficiency	108.75 lm/W
Rated Angle of Reflection	110 Degree
Rated Angle of Reflection 2	50 Degree
UGR	6
Distribution Characteristic 120°	DLS

Light Exit Surfaces	2
Light characteristics	Direct
Light direction	Top, Below

Length	1056 mm
Width	64 mm
Height	1950 mm
Base length	500 mm
Base width	225 mm
Product weight	10980 g
Working Temperature	-20 to 45 °C
Storage Temperature	-40 to 80 °C
IP Protection Class	IP 20
Life Time L70 / B50	50000 h
Switching Cycles	25000
Power Consumption	80 kWh/1000h
Energy Efficiency Class	E

