



<b>Housing Material</b>	Polycarbonate (PC)/iron
<b>Housing Color</b>	Grey
<b>Protection Class</b>	Protection class I/protective grounding
<b>Rated Input</b>	18 W
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz
<b>Power Supply Unit incl.</b>	Yes
<b>Connection Type</b>	Clamp
<b>Number of Cable Entries</b>	2
<b>Cable Gland Diameter</b>	12 mm
<b>Dimmable</b>	No
<b>Motion Detector</b>	No
<b>Light Source</b>	LED, Light source changeable TC
<b>Color Temperature</b>	4000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	2520 lm
<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Below
<b>Length</b>	610 mm
<b>Width</b>	82 mm
<b>Height</b>	75 mm
<b>Working Temperature</b>	-20 to 40 °C
<b>Storage Temperature</b>	-40 to 75 °C
<b>IP Protection Class</b>	IP 65
<b>IK Protection Class</b>	IK08
<b>Life Time L80 / B50</b>	50000 h
<b>Switching Cycles</b>	25000

<b>Power Consumption</b>	18 kWh/1000h
<b>Energy Efficiency Class Lightsource</b>	This product contains a light source of energy efficiency class C.