



Special features

- Including 1 m connecting cable with WEIPU plug

Housing Material	Stainless steel, Die-cast aluminium
Housing Color	Silver
Material of Lens	Glass
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant voltage
Rated Input	5.5 W
Rated Input Voltage	24 V/DC
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	WEIPU plug 2-pole
Secondary Cable Length	1 m
Dimmable	Yes
Control technology	Dimmable via optional controller
Motion Detector	No

Cut Out Diameter	53 mm
Product weight	567 g
Working Temperature	-20 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 67
Load Force max.	5 kN

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	5 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	330 lm
Luminous Efficiency	60 lm/W
Rated Angle of Reflection	24 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Life Time L70 / B50	25000 h
Switching Cycles	100000
Power Consumption	6 kWh/1000h
Energy Efficiency Class	G

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top

Length	66 mm
Width	66 mm
Height	95.5 mm
Installation Depth	132.5 mm