



Product Features

Patch cord, 0,23m, for the connection of DIN-rail mounting devices in an electrical distribution box

- 2 x RJ45
- suitable für Gigabit applications (bandwith 100 MHz)
- 2 x RJ45-plugs
- S/FTP-version
- suitable for all common RJ45 data applications, respectively terminal devices
- fire behavior/Euro-class: EN13501-6:Eca
- mantle material: LSOH, FRNC
- molded bending protection
- bend radius without strain-relief > 25 mm, with strain-relief > 50 mm
- conductor: stranded copper wire, bare Ø 0,42 mm (AWG 27/7)
- according to following standards:
- DIN EN 50173-1
- ISO/IEC 11801
- suitable für PoE+ according to IEEE 802.3at

Features

| General | |
|--------------------------------------|---------------|
| Design | plug/plug |
| shielded | Yes |
| Classification | Cat.5e |
| PoweroverEthernet | Yes |
| Halogen Free | Yes |
| Statistical goods number | 85444210 |
| Country of manufacture | DE |
| GTIN (EAN) | 4043921055939 |
| Dimensions/Weights without packaging | |
| Cable length mm | 230 |
| Net weight piece kg | 0,015 |
| Certifications | |
| WEEE | Yes |
| CE | Yes |
| RoHS conform | Yes |

| Logistics Information | |
|--------------------------|--|
| Packaging | polybag |
| Packaging unit Quantity | 1 |
| Packaging unit Weight kg | 0,017 |
| Packaging unit Width mm | 170 |
| Packaging unit Height mm | 150 |
| Packaging unit Depth mm | 15 |
| References | |
| Accessories | 13910200, 23510300, 23510503, 23510504, 23510505, 23810200 |
| Similar article | 21500005, 21500305, 21500405, 21500505, 21500605, 23510201 |

