



Sometimes it's about more than just light. With our multiple socket tower, available with or without light, another gap in our range is filled. Design your garden even more flexibly, in proven DEKO-LIGHT quality of course and at a price that won't break the bank.

#### Special features

- Safe power distribution outdoors
- Total load max. 3,680 W
- Outlets and lights can be switched on separately
- Connection box with IP67 and accessories including in scope of delivery
- Feed-through wiring possible

|                         |                    |
|-------------------------|--------------------|
| <b>Housing Material</b> | Die-cast aluminium |
| <b>Housing Color</b>    | Grey               |
| <b>Material of Lens</b> | Plastic            |
| <b>Colour of Lens</b>   | White              |

|                                |             |
|--------------------------------|-------------|
| <b>Life Time L70 / B50</b>     | 25000 h     |
| <b>Switching Cycles</b>        | 100000      |
| <b>Power Consumption</b>       | 5 kWh/1000h |
| <b>Energy Efficiency Class</b> | F           |

|                                      |   |
|--------------------------------------|---|
| <b>Protection Class</b>              | Protection class I/protective grounding |
| <b>Rated Input</b>                   | 4.8 W                                   |
| <b>Rated Input Voltage Frequency</b> | 220-240 V/AC 50 / 60 Hz                 |
| <b>Rated Current</b>                 | 16 A                                    |
| <b>Power Supply Unit incl.</b>       | Yes                                     |
| <b>Connection Cable Primary</b>      | Yes                                     |
| <b>Primary Connection</b>            | Connection box IP67                     |
| <b>Dimmable</b>                      | No                                      |
| <b>Motion Detector</b>               | No                                      |

|   |                                  |
|---|----------------------------------|
| <b>Light Source</b>                     | LED, Light source not changeable |
| <b>Color Temperature</b>                | 3000 K                           |
| <b>Colour Consistency</b>               | 6 SDCM                           |
| <b>Colour Rendering Index (Ra)</b>      | 80                               |
| <b>Rated Luminous Flux</b>              | 150 lm                           |
| <b>Rated Angle of Reflection</b>        | 360 Degree                       |
| <b>Distribution Characteristic 120°</b> | NDLS                             |

|                              |        |
|------------------------------|--------|
| <b>Light Exit Surfaces</b>   | 1      |
| <b>Light characteristics</b> | Direct |
| <b>Light direction</b>       | Side   |

|                 |        |
|-----------------|--------|
| <b>Height</b>   | 478 mm |
| <b>Diameter</b> | 100 mm |

|                            |              |
|----------------------------|--------------|
| <b>Working Temperature</b> | -20 to 50 °C |
| <b>Storage Temperature</b> | -10 to 60 °C |
| <b>IP Protection Class</b> | IP 44        |