



Classic design interpreted in a modern way - the ADHARA made from aluminium captivates with its classic lines, ultra-modern materials and high degree of flexibility. The ADHARA can be optimally adjusted to any situation via its two or three joints. Its powerful LED module delivers 950 lumens and can also be dimmed thanks to a touch sensor. Whether for the boss's office or for a child's desk, the ADHARA looks great anywhere.

Special features

- Can be rotated and swivelled via joints
- Dimmable in 3 stages using touch sensor
- High luminous flux
- Ready to use

Housing Material	Aluminium
Housing Color	Black
Material of Lens	Plastic
Protection Class	Protection class II/protective insulation
Rated Input	12 W
Rated Input Voltage Frequency	100-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Cable Primary	Yes
Primary Connection	Power plug
Primary Cable Length	1.6 m
Dimmable	Yes
Control technology	Touch-Sensor
Motion Detector	No

Light Source	LED, Light source not changeable
Lightcolor	Warm white (WW)
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	950 lm
Luminous Efficiency	79.2 lm/W
Rated Angle of Reflection	120 Degree
Distribution Characteristic 120°	DLS

Swivel Angle	135 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	355 mm
Diameter	150 mm
Base height	16 mm
Base diameter	160 mm

Product weight	1460 g
Working Temperature	-5 to 40 °C
Storage Temperature	-20 to 50 °C
IP Protection Class	IP 20
Life Time L70 / B50	25000 h
Switching Cycles	12500
Power Consumption	10 kWh/1000h
Energy Efficiency Class	G