

DSUB SV MA SSDP ANG73-284 09P AU3 NUT M3



| Specification | DSUB SV MA SSDP ANG73-284 09P AU3 NUT M3 |
|--------------------|---|
| HARTING eCatalogue | https://b2b.harting.com/09651237801 |

09 65 123 7801

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Connectors |
|----------------------------|----------------|
| Series | D-Sub |
| Identification | Standard |
| Element | Connector |
| Description of the contact | Stamped Angled |

Part number

Version

| Termination method | Wave soldering termination |
|--------------------|------------------------------|
| Gender | Male |
| Size | D-Sub 1 |
| Connection type | Motherboard to daughtercard |
| Number of contacts | 9 |
| Termination length | 2.9 mm |
| Locking type | Fixing flange with thread M3 |

Technical characteristics

| Distance between rows | 2.84 mm |
|------------------------------------|---------------------|
| Contact spacing (termination side) | 2.74 mm |
| Rated current | 6.5 A |
| Clearance distance | ≥1 mm |
| Creepage distance | ≥1 mm |
| Insulation resistance | >10 ¹⁰ Ω |



Technical characteristics

| Contact resistance | ≤10 mΩ |
|----------------------------------|---------------------------|
| Tightening torque | ≤0.6 Nm Female screw lock |
| Limiting temperature | -55 +125 °C |
| Insertion force | ≤30 N |
| Withdrawal force | ≥3.3 N ≤20 N |
| Performance level | 3 |
| Mating cycles | ≥50 |
| Test voltage U _{r.m.s.} | 1 kV |
| Isolation group | IIIa (175 ≤ CTI < 400) |
| PCB thickness | ≥1.6 mm |
| Installation height | 7.3 mm |
| Hot plugging | No |

Material properties

| Material (insert) | Thermoplastic resin, glass-fibre filled (PBTP) Shell: Plated steel |
|---|--|
| Colour (insert) | Black |
| Material (contacts) | Copper alloy |
| Surface (contacts) | Noble metal over Ni |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | е |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Antimony trioxide Lead Nickel |
| Requirement set with Hazard Levels | R26 |

Specifications and approvals

|--|



Specifications and approvals

UL / CSA UL 1977 ECBT2.E102079

Commercial data

| Packaging size | 100 |
|--------------------------------|------------------------|
| Net weight | 7.77 g |
| Country of origin | Romania |
| European customs tariff number | 85366990 |
| GTIN | 5713140076860 |
| eCl@ss | 27440214 D-Sub coupler |