



QualityFlex Performance flex lighting 10 m, CRI > 95, 10 W / m, IP00

Artikel-Nr. 19303104



QualityFlex Performance flex lighting 10 m, CRI > 95, 10 W / m, IP00, white, 4.000K, CRI > 95. LED flex lighting for decorative, technical as well as efficient lighting of light coves, linear applications and backlighting, basic or general lighting of rooms, architectural applications and for areas where high illumination is required, such as indirect or direct lighting, luminous ceilings, gastronomy lighting and much more. Länge: 10000.0 mm Lampenleistung je Meter: 10.0 W/m, Lichtstrom je Meter: 900.0 lm/m, Schutzart raumseitig: IP00, Schutzklasse: III, Spannung: 24V DC, Abstrahlwinkel: 120.0 °, 120 LEDs pro Meter, Chip-Abstand (Short Pitch) : 8,3mm. Zur Individuellen Anwendung kann die LED-Flexplatine alle 50 mm eingekürzt werden. Die maximale Systemlänge von 10.000mm darf mit einer Einspeisung nicht überschritten werden.

Artikel-Nr.	19303104
Stand:	06.12.2021 17:26

Colour temperature	4000 K
Light colour	White
Luminous flux per meter	900 lm/m
Power	100 W
Lamp power per meter	10 W/m
Beam angle	120 °
Length	10,000 mm
Width	10 mm
Aufbauhöhe	1.4 mm
Length of individual sections	50 mm
Degree of protection	IP00
Protection class	III

McAdam-Step	McAdam-Step 5
Short Pitch	8.3 mm
Number of lamps per meter	120 Qty
Voltage	24V
Voltage type	DC
Ambient temperature	-10 °C bis +40 °C
Control	Dimming depending on driver
Circuit type	Parallel conduction
Length of the connection line	350 mm
Colour rendering	CRI > 95
Maximum module length	10,000 mm