



Modern elegance for ceilings; the ceiling lights from the SCULPTORIS series can be used in a number of ways indoors thanks to different outputs, sizes and colour temperatures. The surface-mounted ceiling lights provide extensive illumination for rooms and also look great as wall lights.

The light is softly and extensively diffused through the large, circumferential diffuser with matt aluminium design and illuminates rooms pleasantly and evenly.

#### Special features

- Light colour adjustable in 2 stages
- Uniform illumination
- Circumferential diffuser

<b>Housing Material</b>	Aluminium	<b>Life Time L70 / B50</b>	30000 h
<b>Housing Color</b>	White	<b>Switching Cycles</b>	20000
<b>Housing Surface</b>	Matt	<b>Power Consumption</b>	60 kWh/1000h
<b>Material of Lens</b>	Acryl	<b>Energy Efficiency Class Lightsource</b>	This product contains a light source of energy efficiency class F.
<b>Surface Structure of Lens</b>	Satined		
<b>Protection Class</b>	Protection class I/protective grounding		
<b>Rated Input</b>	60 W		
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Dimmable</b>	Yes		
<b>Control technology</b>	Leading-edge dimmer, Trailing-edge dimmer		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source changeable TC		
<b>Color Temperature</b>	3000/4000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	4100/4200 lm		
<b>Rated Luminous Flux 2</b>	4200 lm		
<b>Rated Angle of Reflection</b>	150 Degree		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Below		
<b>Height</b>	130 mm		
<b>Diameter</b>	800 mm		
<b>Working Temperature</b>	-10 to 45 °C		
<b>Storage Temperature</b>	-10 to 45 °C		
<b>IP Protection Class</b>	IP 20		