

Wall mounting socket outlet - housing dimensions 126x83



| Product description | |
|---------------------------|-----------------------------|
| BALS-Prd.-Nr | 1149 |
| EAN | 4024941011495 |
| Product category | Wall mounting socket outlet |
| Current | 32A |
| Number of poles | 4p |
| Poles | 3P+PE |
| Position of earth contact | 6 h |
| Voltage | 380 up to 415V |
| Frequency | 50 and 60Hz |

| Product description | |
|------------------------|--|
| Protection degree | IP67 |
| Colour code | red RAL 3000 |
| Colour of appliance | Hinged lid red RAL 3000, Bayonet ring grey RAL 7035, Housing bottom grey RAL 7035, Housing top grey RAL 7035 |
| Connection design | with screw terminal |
| Maximum conductor size | 10,0 qmm |
| Cable entry | 1xM25 top, 2xM25 bottom |
| Height | 161mm |
| Width | 94mm |
| Depth | 139mm |
| Dimension of enclosure | 126x83 mm (HxW) |
| Material of enclosure | Polyamide |
| Contact | The contact carrier is made of polyamide, The contacts are brass |

| Additional technical properties | |
|---------------------------------|---|
| | The cable entry is one at top open and two at bottom closed |
| | Lower part of housing rotatable by 180° |
| | 4 cut out fixing holes |

| Logistics data | |
|----------------|-----------------|
| Weight/pcs | 0.44 kg / Piece |

| Logistics data | |
|----------------|---------------|
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941011495 |
| Length | 139 mm |
| Width | 94 mm |
| Height | 161 mm |
| Weight | 0.441 kg |
| Volume | 2,103.626 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941827355 |
| Length | 335 mm |
| Width | 283 mm |
| Height | 268 mm |
| Weight | 4.75 kg |
| Volume | 21,937.5 ccm |



1 MB 13

| Ampere Polzahl | 16 3 | 16 4 | 16 5 | 32 3 | 32 4 | 32 5 |
|----------------------------|---------|---------|---------|---------|---------|---------|
| a | 64,0 | 75,0 | 75,0 | 83,0 | 83,0 | 83,0 |
| b | 87,0 | 100,0 | 100,0 | 126,0 | 126,0 | 126,0 |
| c | 115,0 | 130,0 | 130,0 | 160,0 | 160,0 | 160,0 |
| d | 103,0 | 110,0 | 115,0 | 129,0 | 129,0 | 135,0 |
| e | 51,0 | 59,0 | 59,0 | 68,0 | 68,0 | 68,0 |
| f | 20,0 | 11,0 | 11,0 | 11,0 | 11,0 | 11,0 |
| g | 20,0 | - | - | - | - | - |
| h ø | 4,1 | 5,1 | 5,1 | 5,5 | 5,5 | 5,5 |
| i | 4,5 | 4,5 | 4,5 | 6,5 | 6,5 | 6,5 |
| k ø | 8,0 | 10,0 | 10,0 | 12,0 | 12,0 | 12,0 |
| l | - | - | - | 65,0 | 65,0 | 65,0 |
| m | - | - | - | 80,0 | 80,0 | 80,0 |
| n ø | - | - | - | 10,0 | 10,0 | 10,0 |
| o | M20 | M20 | M20 | M25 | M25 | M25 |
| p | für M20 | für M20 | für M20 | 2 x M25 | 2 x M25 | 2 x M25 |
| Leiter mm ² min | 1,5 | 1,5 | 1,5 | 2,5 | 2,5 | 2,5 |
| Leiter mm ² max | 4 | 4 | 4 | 10 | 10 | 10 |