

**Special features**

- Including 0.5 m connecting cable

|                                      |                                         |
|--------------------------------------|-----------------------------------------|
| <b>Housing Material</b>              | Stainless steel, Die-cast aluminium     |
| <b>Housing Color</b>                 | Silver                                  |
| <b>Material of Lens</b>              | Glass                                   |
| <b>Protection Class</b>              | Protection class I/protective grounding |
| <b>Rated Input</b>                   | 7.8 W                                   |
| <b>Rated Input Voltage Frequency</b> | 220-240 V/AC 50 / 60 Hz                 |
| <b>Power Supply Unit incl.</b>       | Yes                                     |
| <b>Connection Cable Primary</b>      | Yes                                     |
| <b>Primary Connection</b>            | Connection box                          |
| <b>Primary Cable Length</b>          | 0.5 m                                   |
| <b>Dimmable</b>                      | No                                      |
| <b>Motion Detector</b>               | No                                      |

|                                         |                                  |
|-----------------------------------------|----------------------------------|
| <b>Light Source</b>                     | LED, Light source not changeable |
| <b>Color Temperature</b>                | 3000 K                           |
| <b>Colour Consistency</b>               | 5 SDCM                           |
| <b>Colour Rendering Index (Ra)</b>      | 80                               |
| <b>Rated Luminous Flux</b>              | 720 lm                           |
| <b>Luminous Efficiency</b>              | 92.3 lm/W                        |
| <b>Rated Angle of Reflection</b>        | 25 Degree                        |
| <b>Light Distribution</b>               | Symmetric                        |
| <b>Distribution Characteristic 120°</b> | DLS                              |

|                              |        |
|------------------------------|--------|
| <b>Light Exit Surfaces</b>   | 1      |
| <b>Light characteristics</b> | Direct |
| <b>Light direction</b>       | Top    |

|                           |        |
|---------------------------|--------|
| <b>Height</b>             | 102 mm |
| <b>Diameter</b>           | 116 mm |
| <b>Installation Depth</b> | 150 mm |
| <b>Cut Out Diameter</b>   | 102 mm |
| <b>Product weight</b>     | 805 g  |

|                                |              |
|--------------------------------|--------------|
| <b>Working Temperature</b>     | -20 to 40 °C |
| <b>Storage Temperature</b>     | -10 to 60 °C |
| <b>IP Protection Class</b>     | IP 67        |
| <b>Load Force max.</b>         | 20 kN        |
| <b>Life Time L70 / B50</b>     | 30000 h      |
| <b>Switching Cycles</b>        | 100000       |
| <b>Power Consumption</b>       | 8 kWh/1000h  |
| <b>Energy Efficiency Class</b> | E            |