



With the new very high-quality D FLEX LINE series, the DEKO-LIGHT range now includes flexible LED strip lights that facilitate homogeneous, spot-free illumination thanks to their special construction. In order to achieve this, the D FLEX LINE strip lights are fully encapsulated in light-fast polyurethane. Whether for rounded counters, furniture items, equipment of any type, advertising signs or objects in events and catering environments - these strip lights are excellent when it comes to setting the scene with round or curved shapes and generating homogeneous linear light, similar to a neon light rod. They are available in two light emission directions: to the side or upwards depending on bending option.

Special features

- Spot-free homogeneous illumination
- Very easy installation - using adapted profile
- UV and salt water-resistant IP68
- Ultra-flexible and therefore very versatile to use
- Light-fast polyurethane encapsulation

Housing Material	Polyurethan
Housing Color	White
Housing Surface	Satinised
Surface Structure of Lens	Satined
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant voltage
Rated Input 1m	10.5 W
Rated Input Voltage	24 V/DC
Power Supply Unit incl.	No
Connection Cable Primary	Yes
Primary Connection	With free strand / conductor ends
Primary Cable Length	3 m
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Secondary Cable Length	3 m
Dimmable	Yes
Control technology	Dimmable via optional controller
Number of Channels	1

LED Distance	6.94 mm
Length	5000 mm
Width	12 mm
Height	20 mm
Product weight	1500 g
Working Temperature	-25 to 45 °C
Storage Temperature	-25 to 60 °C
IP Protection Class	IP 68/max. 2 m
Type of IP Protection	PVC cover
Life Time L70 / B50	60000 h
Switching Cycles	30000
Power Consumption	11 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Lightcolor	Warm white (WW)
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Angle of Reflection	125 Degree
Distribution Characteristic 120°	NDLS
Luminous Flux 1m	368 lm
Luminous Efficiency 1m	35.05 lm/W
LED/Meter	60
Bending Radius min.	150 mm
Total Length to be Operated max.	5 m
Segment Length	100 mm
Segment LED Quantity	6