



Special features

- Including 1 m connecting cable
- Including honeycomb filter

Housing Material	Stainless steel, Die-cast aluminium
Housing Color	Silver
Material of Lens	Glass
Protection Class	Protection class I/protective grounding
Rated Input	18.4 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Cable Primary	Yes
Primary Connection	Connection box
Primary Cable Length	1 m
Dimmable	No
Motion Detector	No

Working Temperature	-20 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 67
Load Force max.	20 kN

Life Time L70 / B50	35000 h
Switching Cycles	20000
Power Consumption	19 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	5 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	770 lm
Luminous Efficiency	41.8 lm/W
Rated Angle of Reflection	25 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Swivel Angle	30 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top

Height	190 mm
Diameter	250 mm
Installation Depth	220 mm
Cut Out Diameter	222 mm
Product weight	4688 g