



#### Product Features

ClassEA iso U-jack, unshielded, double, flush mounting, with plastic mounting brackets, with spreading claws, pure white (similar RAL 9010)
- for use in 10 Gigabit-Ethernet-Networks (transmission bandwidth 500 MHz)
- quick installation via LSA-contacts
- RJ45-openings slanted downwards
- with plastic mounting brackets
- with spreading claws
- colour code T568A and T568B according to TIA / EIA-568-B.2
- suitable for Cat.6 and Cat.7 cables (Ø 6-10 mm)
- UPOE conform
- HDBaseT conform
- LSA-contacts for one wire 0,4-0,63 mm Ø, AWG 26-22, maximum number of connections > 50-times
- suitable for PoE++ / 4PPoE according to IEEE 802.3bt
- UPOE conform
- HDBaseT conform
- suitable for the UAE-design wall plates of all well-known manufacturer (Berker, Busch-Jäger, GIRA, JUNG, Merten etc.)
- according to the following standards:
- ISO/IEC 11 801, ClassEA, unshielded
- RJ11/12 protected against mismatching
- ANSI TIA/EIA-568-C.2, ClassEA
- life > 750 cycles

#### Features

General	
Cover plate	Yes
Centre plate	Yes
Design	jack
Design capability	Yes
Labeling field	Yes
Classification	ClassEA iso U
PoweroverEthernet	Yes
Halogen Free	Yes
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921661963
Mounting types	
floor outlet box/underfloor installation	Yes
flush-mounted	Yes

trunking installation	Yes
Dimensions/Weights without packaging	
Length mm	80
Width mm	80
Height mm	31
Net weight piece kg	0,043
Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	10
Packaging unit Weight kg	0,54
Packaging unit Width mm	144
Packaging unit Height mm	165
Packaging unit Depth mm	83
References	
Accessories	10010001, 10010051, 10010055, 10010056, 13510002, 13510003, 13510052, 13510053, 13510503, 13510505, 13511503, 232101100, 39200000, 39200002
Similar article	132112010, 13700300, 138112070

