lightnet

Plank-P4

Pendant luminaire - Direct/indirect light distribution



Illustrations may only be similar and serve as an orientation.

Plank-P4. LED. Pendant luminaire. Luminaire body made of high-quality aluminum profile. Surface finish Jet Black. Direct/indirect light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=19. Switchable. LxWxH (rectangular). L=1210mm. W=231mm. H=25mm. Y-cord suspension with power supply cable and ceiling rose (Set). Pendant length max 1500mm. Power supply: transparent.

Ceiling rose: Matching luminaire's surface colour. Medium-power current. 3544lm. 33W. 7,5kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.

Article code: JP4ABE-830M-L1210-Y

lightnet


Plank-P4

Pendant luminaire - Direct/indirect light distribution

Article code: JP4ABE-830M-L1210-Y







Productname Plank-P4 Lamp LED

Installation Type Pendant luminaire

Surface finish Jet Black

Light characteristics Direct/indirect light distribution

Colour temperature 3000K Colour Rendering Index (CRI) CRI>80

Optical system Microprismatic screen

Control Switchable
Length L/Diameter D (mm) L=1210mm
Width W (mm) W=231mm
Height H (mm) H=25mm
Current/Power Medium-Power
Luminous Flux 3544lm

Luminous Flux 3544lm Power consumption 33W

Suspension Y-susp. (Set)

Ceiling rose colour Ceiling rose: Matching luminaire`s

surface colour

Pendant length (mm) Pendant length max 1500mm

Degree of protection IP20

Cable Colour Power supply: transparent LED lifetime L85B10 (tq 25°C) = 50.000h

UGR UGR<=19
Photometric code 8 30 / 3 3 9
Photobiological class RG0 (EN62471)

Indoor/Outdoor Indoor: ta [ambient] max. 25°C

Weight (kg) 7,5kg























