

lightnet

Matric-R3

Pendant light-line - Direct/indirect light distribution

Article code: LR3OBL-830H-L2055-Y



Illustrations may only be similar and serve as an orientation.

Matric-R3. LED. Pendant light-line. Luminaire body made of high-quality aluminum profile. Surface finish Jet Black. Direct/indirect light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. Dimmable DALI. LxWxH (rectangular). L= 2055mm. W=55mm. H=85mm. Y-cord suspension with power supply cable and ceiling rose (Set). Pendant length max 1500mm. Power supply: transparent. Ceiling rose:

Matching luminaire's surface colour. High-power current. 11575lm. 98W. 7,3kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.

Matric-R3

Pendant light-line - Direct/indirect light distribution

Article code: LR3OBL-830H-L2055-Y



Customer / Project: _____

Note: _____

Productname	Matric-R3
Lamp	LED
Installation Type	Pendant light-line
Surface finish	Jet Black
Light characteristics	Direct/indirect light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Opal diffuser
Control	Dimmable (DALI)
Length L/Diameter D (mm)	L=2055mm
Width W (mm)	W=55mm
Height H (mm)	H=85mm
Current/Power	High-Power
Luminous Flux	11575lm
Power consumption	98W
Suspension	Y-susp. (Set)
Ceiling rose colour	Ceiling rose: Matching luminaire`s surface colour
Pendant length (mm)	Pendant length max 1500mm
Degree of protection	IP20
Certification	Prüfzeichen: ENEC
Cable Colour	Power supply: transparent
LED lifetime	L80B10 (tq 25°C) = 50.000h
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	7,3kg

