

**Special features**

- Including 0.5 m connecting cable

Housing Material	Stainless steel
Housing Color	Silver
Material of Lens	Glass
Protection Class	Protection class I/protective grounding
Rated Input	7.6 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Cable Primary	Yes
Primary Connection	Connection box
Primary Cable Length	0.5 m
Dimmable	No
Motion Detector	No

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	540 lm
Luminous Efficiency	71.1 lm/W
Rated Angle of Reflection	20 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top

Height	111 mm
Diameter	173 mm
Installation Depth	150 mm
Cut Out Diameter	157 mm
Product weight	1815 g

Working Temperature	-20 to 50 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 67
Load Force max.	5 kN
Life Time L70 / B50	30000 h
Switching Cycles	100000
Power Consumption	8 kWh/1000h
Energy Efficiency Class	F