

## Plug - with screwless terminals, for harsh applications



| Product description       |                       |
|---------------------------|-----------------------|
| BALS-Prd.-Nr              | 210764                |
| EAN                       | 4024941190015         |
| Product category          | QUICK-CONNECT TE plug |
| Current                   | 63A                   |
| Number of poles           | 4p                    |
| Poles                     | 3P+PE                 |
| Position of earth contact | 7 h                   |
| Voltage                   | 480 up to 500V        |
| Frequency                 | 50 and 60Hz           |

| Product description    |  |
|------------------------|--|
| Protection degree      | IP67   |
| Colour code            | black RAL 9005   |
| Colour of appliance    | Collar black RAL 9005, Bayonet ring grey RAL 7035, Cable gland grey RAL 7035, Housing cover black RAL 9005 |
| Connection design      | screwless spring-clamp technology with box terminals   |
| Maximum conductor size | 16,0 qmm   |
| Cable entry            | Cable gland  |
| Height                 | 234mm  |
| Width                  | 114mm  |
| Depth                  | 114mm  |
| Material of enclosure  | Polyamide  |
| Contact                | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated   |

| Additional technical properties |  |
|---------------------------------|--|
|                                 | For cable diameter from 16 up to max. 36 mm, Screwless housing connection, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings |

| Logistics data |                 |
|----------------|-----------------|
| Weight/pcs     | 0.72 kg / Piece |
| Packaging      | Bag             |
| Content amount | 1 ST            |

| Logistics data |               |
|----------------|---------------|
| EAN            | 4024941190015 |
| Length         | 114 mm        |
| Width          | 114 mm        |
| Height         | 234 mm        |
| Weight         | 0.721 kg      |
| Volume         | 3,041.064 ccm |
| Packaging      | Carton        |
| Content amount | 5 ST          |
| EAN            | 4024941946094 |
| Length         | 325 mm        |
| Width          | 217 mm        |
| Height         | 210 mm        |
| Weight         | 3.806 kg      |
| Volume         | 13,588.4 ccm  |



| Ampere Polzahl             | 63<br>3 | 63<br>4 | 63<br>5 |  |  |  |
|----------------------------|---------|---------|---------|--|--|--|
| a ø                        | 113,5   | 113,5   | 113,5   |  |  |  |
| b                          | 153,0   | 153,0   | 153,0   |  |  |  |
| c                          | 233,0   | 233,0   | 233,0   |  |  |  |
| d                          | 171,0   | 171,0   | 171,0   |  |  |  |
| e ø                        | 36,0    | 36,0    | 36,0    |  |  |  |
| Leiter mm <sup>2</sup> min | 6       | 6       | 6       |  |  |  |
| Leiter mm <sup>2</sup> max | 16      | 16      | 16      |  |  |  |
|                            |         |         |         |  |  |  |
|                            |         |         |         |  |  |  |
|                            |         |         |         |  |  |  |
|                            |         |         |         |  |  |  |