

Wall mounting socket outlet - with external fixing



| Product description | |
|-------------------------------|-----------------------------|
| BALS-Prd.-Nr | 11651 |
| EAN | 4024941116510 |
| product category (PG) | Wall mounting socket outlet |
| current (A) | 32A |
| number of poles (P99) | 3p |
| number of poles (P) | 2P+PE |
| position of earth contact (H) | 6 h |
| voltage (V) | 200 up to 250V |
| frequency (HZ) | 50 and 60Hz |

| Product description | |
|-----------------------------|---|
| protection degree (SA) | IP44 |
| colour code 1 (KF1) | blue RAL 5015 |
| Colour of appliance | Collar blue RAL 5015, Hinged lid blue RAL 5015, Housing bottom grey RAL 7035, Housing top grey RAL 7035 |
| connection design (AT) | with screw terminal |
| maximum conductor size (LQ) | 10,0 qmm |
| cable entry (KE) | top entry M25 |
| Height | 143mm |
| Width | 94mm |
| Depth | 103mm |
| dimension of enclosure (GG) | 92x94 mm (HxW) |
| material of enclosure (GM) | Polyamide |
| contact | The contact carrier is made of polyamide, The contacts are brass |

| Additional technical properties | |
|---------------------------------|---|
| | The cable entry is one at top open and one at bottom closed |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.272 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |

| Logistics data | |
|----------------|---------------|
| EAN | 4024941116510 |
| Length | 103 mm |
| Width | 94 mm |
| Height | 143 mm |
| Weight | 0.273 kg |
| Volume | 1,384.526 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941840682 |
| Length | 325 mm |
| Width | 217 mm |
| Height | 210 mm |
| Weight | 2.926 kg |
| Volume | 13,588.4 ccm |



| Ampere Polzahl | 16 3 | 16 4 | 16 5 | 32 3 | 32 4 | 32 5 |
|----------------------------|---------|---------|---------|---------|---------|---------|
| a | 59,5 | 72,4 | 72,4 | 79,1 | 79,1 | 79,1 |
| b | 90,0 | 90,0 | 90,0 | 92,0 | 92,0 | 92,0 |
| c | 130,0 | 130,0 | 131,0 | 142,0 | 142,0 | 142,0 |
| d | 85,0 | 96,0 | 98,0 | 103,0 | 103,0 | 106,0 |
| e | 62,0 | 77,0 | 77,0 | 84,0 | 84,0 | 84,0 |
| f | 33,5 | 33,5 | 33,5 | 30,0 | 30,0 | 30,0 |
| h | 9,0 | 9,0 | 9,0 | 9,0 | 9,0 | 9,0 |
| i | 5,5 | 5,5 | 5,5 | 5,5 | 5,5 | 5,5 |
| k | 8,0 | 9,0 | 9,0 | 9,0 | 9,0 | 9,0 |
| l ø | 21,0 | 21,0 | 21,0 | 21,0 | 21,0 | 21,0 |
| m | 72,0 | 87,0 | 87,0 | 94,0 | 94,0 | 94,0 |
| n | M20 | M25 | M25 | M25 | M25 | M25 |
| Leiter mm ² min | 1,5 | 1,5 | 1,5 | 2,5 | 2,5 | 2,5 |
| Leiter mm ² max | 4 | 4 | 4 | 10 | 10 | 10 |

1 MB 19