



<b>Housing Material</b>	PP - Polypropylene	<b>IP Protection Class</b>	IP 54
<b>Housing Color</b>	Black	<b>IK Protection Class</b>	IK08
<b>Housing Surface</b>	Matt		
<b>Colour of Lens</b>	White	<b>Life Time L70 / B50</b>	50000 h
<b>Surface Structure of Lens</b>	Opal	<b>Switching Cycles</b>	100000
		<b>Power Consumption</b>	3 kWh/1000h
<b>Protection Class</b>	Protection class II/protective insulation	<b>Energy Efficiency Class Lightsource</b>	This product contains a light source of energy efficiency class C.
<b>Rated Input</b>	3 W		
<b>Rated Input Voltage Frequency</b>	200-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Dimmable</b>	No		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source changeable TC		
<b>Color Temperature</b>	3000/4000 K		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	250/260 lm		
<b>Rated Luminous Flux 2</b>	260 lm		
<b>Rated Angle of Reflection</b>	120 Degree		
<b>Light Distribution</b>	Symmetric		
<b>Distribution Characteristic 120°</b>	DLS		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Front		
<b>Length</b>	275 mm		
<b>Width</b>	275 mm		
<b>Height</b>	64 mm		
<b>Base height</b>	14 mm		
<b>Base diameter</b>	245 mm		
<b>Working Temperature</b>	-20 to 50 °C		
<b>Storage Temperature</b>	-20 to 60 °C		