BRUMBERG

FIBATEC LED RGB starry sky set

Article no. 48224001





Tender

LED RGB starry sky set. Comprising: 1 x projector - 1 W LED-RGB multi-color (L 180 x W 65 x H 35 mm), including a converter for connection with the 230-V mains voltage, 1 x fiber bundle, customised, 100-component: 30 x Ø 0.5 mm, 40 x Ø 0.75 mm, 20 x Ø 1.0 mm, 10 x Ø 1.5 mm, Length: 1,500 mm each 1 x radio remote control, range (visual contact): approximately 5 m, functions: switch - on/off switchable, program selection, direct selection of static colors, brightness adjustment, including 1,500 mm connection cable with Schuko plug, without fan (thus no noise generation). The set has been designed for an area of approximately 2 m². Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 1W, Light colour : RGB, With control gear: Yes, Control: Wireless technology control.

Article data	
Article no.	48224001
GTIN	4250047704249
Series name	FIBATEC
Short description	LED RGB starry sky set
Innendurchmesser Faseraufnahme	30 mm
Scope of delivery	Lieferung inkl. RGBW Funkfernbedienung
Weight	0.980 kg
Length of the connection line	1,500 mm

Lighting technology	
Light generator output	1 W
Colour temperature	RGB
Light colour	RGB

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 10.05.2022 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/

Light. For Generations.

BRUMBERG

FIBATEC LED RGB starry sky set

Article no. 48224001

Light. For Generations.

Operating technology of the luminaire	
AC nominal voltage max	230 V
Frequenz max.	50 Hz
Lamp	LED
Protection class	
Degree of protection	IP20
Ambient temperature	0 bis 40 °C
Control	Wireless technology control
Length of the connection line	1,500 mm
Bulb change possible	Yes
Radio range	5 m
Transmission frequency	869.5 MHz

Packing data	
Gross weight	1.39 kg
Length of packaging	300 mm
Packaging width	300 mm
Packaging hight	180 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.