



MENKAR series pendant lamps impress with clever lighting functions and high-quality aluminium accents. The rear light, which can be switched on separately (approx. 15-20 % of indirect lighting component), allows continuous indirect lighting whilst the main light can be switched on at any time.

Special features

- Indirect and direct lighting
- Light colour adjustable in 2 stages
- Indirect lighting can be switched on separately
- Suspended mounting up to 1800 mm
- High luminous intensity

| | | | |
|--------------------------------------|---|---|---|
| Housing Material | Aluminium | Working Temperature | -10 to 45 °C |
| Housing Color | White | Storage Temperature | -10 to 45 °C |
| Housing Surface | Matt | IP Protection Class | IP 20 |
| Material of Lens | Acryl | Life Time L70 / B50 | 30000 h |
| Surface Structure of Lens | Satined | Switching Cycles | 20000 |
| Protection Class | Protection class I/protective grounding | Power Consumption | 90 kWh/1000h |
| Rated Input | 90 W | Energy Efficiency Class Lightsources | This product contains light sources of energy efficiency classes E and F. |
| Rated Input Voltage Frequency | 220-240 V/AC 50 / 60 Hz | | |
| Power Supply Unit incl. | Yes | | |
| Connection Type | Clamp | | |
| Dimmable | Yes | | |
| Control technology | Leading-edge dimmer, Trailing-edge dimmer | | |
| Motion Detector | No | | |
| Light Source | LED, Light source changeable TC | | |
| Color Temperature | 3000/4000 K | | |
| Colour Consistency | 6 SDCM | | |
| Colour Rendering Index (Ra) | 80 | | |
| Rated Luminous Flux | 8400/8700 lm | | |
| Rated Luminous Flux 2 | 8700 lm | | |
| Light Distribution | Symmetric | | |
| Light Exit Surfaces | 2 | | |
| Light characteristics | Direct, Indirect | | |
| Light direction | Top, Below | | |
| Height | 90 mm | | |
| Diameter | 800 mm | | |
| Base height | 40 mm | | |
| Base diameter | 150 mm | | |
| Pendulum Length max. | 3000 mm | | |