



#### Product Features

- Patch cord, Cat.6A iso, 3 m green (similar RAL 6016)
- suitable für 10-Gigabit applications (bandwith 500 MHz)
- 2 x RJ45-plugs
- S/FTP-version
- suitable for all common RJ45 data applications, respectively terminal devices
- fire behavior/Euro-class: EN13501-6:Eca
- mantle material: LSOH, FRNC
- molded bending protection
- bend radius without strain-relief > 25 mm, with strain-relief > 50 mm
- conductor: stranded copper wire, bare Ø 0,42 mm (AWG 27/7)
- according to following standards:
- DIN EN 50173-1
- ISO/IEC 11801
- suitable für PoE+ according to IEEE 802.3at

#### Features

General	
shielded	Yes
Classification	Cat.6A iso
PoweroverEthernet	Yes
Halogen Free	Yes
Statistical goods number	85444110
Country of manufacture	DE
GTIN (EAN)	4043921666180
Dimensions/Weights without packaging	
Cable length mm	3.000
Net weight piece kg	0,105
Certifications	
WEEE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	polybag
Packaging unit Quantity	1
Packaging unit Weight kg	0,108
Packaging unit Width mm	255
Packaging unit Height mm	195
Packaging unit Depth mm	15

References	
Accessories	136104030, 136104070, 136112030, 136112070, 13900304
Similar article	21200030, 21500030, 21500330, 21500430, 21500530, 21600030, 23510201, 23510202