






OREN LED panel 1245 x 308 mm MP DALI-2
 Article no. 32061074



Tender
 LED panel 1245 x 308 mm MP DALI-2, Rectangular. Recessed luminaire for ceilings with visible mounting rails. Ceiling cut-out L x W 1227 x 290 mm, Installation depth 40 mm, Length 1.245 mm, Width 308 mm, Weight 3,5 kg, with rotationssymmetrical, deep, wide distributed light intensity. Cover plastic, microprismatic. Luminous flux 4.700 lm, UGR < 19, Power 1 x 33 W, Light colour neutral white, Correlated color temperature (CCT) 4.000 K, Colour rendering index CRI > 80, Rated life time L70/B10 at 25 °C: 110.000 h, Rated life time L70/B50 at 25 °C: 125.000 h, Rated life time L80/B10 at 25 °C: 78.000 h, Rated life time L80/B50 at 25 °C: 100.000 h, Housing material: Aluminium / PMMA, Colour: white matt, Permissible ambient temperature (ta): -20°C to +45°C, Protection class (EN 61140): II, Degree of protection (DIN EN 60529): IP20, shock resistance according to IEC62262: IK04. With electronic driver, DALI-2 dimmable. Additionally this luminaire is ENEC-proofed by an independent laboratory.


OREN LED panel 1245 x 308 mm MP DALI-2

Article no. 32061074

Article data	
Article no.	32061074
GTIN	4251433998334
Series name	OREN
Short description	LED panel 1245 x 308 mm MP DALI-2
Material	Aluminium / PMMA
Colour	white matt
Shape	Rectangular
Length	1,245 mm
Width	308 mm
Built-in length	1227 mm
Built-in width	290 mm
Installation depth	40 mm
Hight	11 mm
Scope of delivery	incl. multilumen DALI-2 / PUSH-dimm driver. 300 mA bis 1.050 mA (in steps of 50)
Weight	3.5 kg
stamp	ENEC
Conformance	CE, UKCA

Lighting technology	
Colour temperature	4.000 K
Light colour	white
Light output	Direct
Luminous flux	4,700 lm
System efficiency	124 lm/W
McAdam-Step	McAdam-Step 3
Colour rendering	CRI > 80
Reflector	Without
Beam angle	85°
Glare evaluation	UGR < 19
Light sharing	Symmetric
Photobio. Risk group according to EN 62778	RG0
Adjustable color temperature	No


OREN LED panel 1245 x 308 mm MP DALI-2

Article no. 32061074

Operating technology of the luminaire	
System output	38 W
Voltage type	AC/DC
AC nominal voltage min	198 V
AC nominal voltage max	264 V
DC nominal voltage min	176 V
DC nominal voltage max	276 V
Frequency max	60 Hz
Frequency min	50 Hz
Lamp	LED
Lamp holder	Without fitting
Protection class	II
Degree of protection	IP20
Ambient temperature	-20°C to +45°C
Dimmable	Yes
Control	DALI-2 , PUSH-Dimm
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.
Glow wire test according to IEC 60695-2-12	650°C
Rated life time L70/B50 at 25 °C	125.000 h
Rated life time L80/B10 at 25 °C	78.000 h
Rated life time L80/B50 at 25 °C	100.000 h
Rated life time L90/B10 at 25 °C	30.000 h
Energy efficiency class	not required
max. no. lights on B16 A	59
max. no. lights on C10 A	37
max. no. lights on C16 A	59

Operating technology of the luminaire	
Hight	11 mm
Lamp holder	Without fitting
Power	38 W
Voltage type	DC
Current	1.050 mA
Lamp	LED
Protection class	III
Degree of protection	IP40
Rated life time L70/B50 at 25 °C	100,000 h
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Impact resistance	IK04
Further references	No cover with thermal insulation material
Material cover	Plastic, microprismatic
Suitable for through-wiring	Yes


OREN LED panel 1245 x 308 mm MP DALI-2

Article no. 32061074

Packing data	
Gross weight	3.9 kg
Length of packaging	1,270 mm
Packaging width	360 mm
Packaging height	35 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.

Optional accessories	
Article no.: 81032063 Installation frame 1-piece, 1,303 x 366 x 30 mm, white Dimensions: 1,300 mm x 365 mm x 30 mm https://www.brumberg.com/fileadmin/products/Datenblatt_81032063_2021_DE.pdf	
Article no.: 81032064 Mounting frame 4-piece, 1,265 x 328 x 50 mm, white Dimensions: 1,265 mm x 325 mm x 50 mm https://www.brumberg.com/fileadmin/products/Datenblatt_81032064_2021_DE.pdf	
Article no.: 81032069 Y-rope suspension set of 1 300/308mm Dimensions: 2,000 mm https://www.brumberg.com/fileadmin/products/Datenblatt_81032069_2021_DE.pdf	
Article no.: 00532900 Installation spring set of 4 for LED panel https://www.brumberg.com/fileadmin/products/Datenblatt_00532900_2021_DE.pdf	
Article no.: 17840010 LED driver 800 mA - 1,050 mA, on/off, for through-wiring Leistung: 42 W Dimensions: 170 mm x 65 mm x 30 mm https://www.brumberg.com/fileadmin/products/Datenblatt_17840010_2021_DE.pdf	
Article no.: 17843010 LED driver 1,050 mA, trailing edge dimmable Leistung: 39,9 W Dimensions: 142.3 mm x 31.5 mm x 60 mm https://www.brumberg.com/fileadmin/products/Datenblatt_17843010_2021_DE.pdf	
Article no.: 17844010 LED driver 900 mA - 1,050 mA, 1-10 V dimmable Leistung: 44,1 W Dimensions: 180 mm x 40 mm x 30 mm https://www.brumberg.com/fileadmin/products/Datenblatt_17844010_2021_DE.pdf	