

preLink Terminal mod AWG22/24 black 1=10



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 20 82 000 0005 |
| Specification | preLink Terminal mod AWG22/24 black 1=10 |
| HARTING eCatalogue | https://harting.com/20820000005 |

Identification

| | |
|---------------|---------------------------|
| Category | Connectors |
| Series | preLink® |
| Element | Termination block |
| Specification | 4 poles AIDA compliant |

Version

| | |
|--------------------|--|
| Termination method | preLink® IDC insulation displacement termination |
| Pack contents | 10 pieces |

Technical characteristics

| | |
|-------------------------------|---|
| Conductor cross-section | 0.22 ... 0.32 mm ² |
| Conductor cross-section [AWG] | AWG 24 ... AWG 22 |
| Wire outer diameter | 1.3 ... 1.6 mm |
| Limiting temperature | -40 ... +85 °C |
| Mating cycles | ≥10 |
| Vibration resistance | 5.72 m/s ² acc. to IEC 61373 Category 1 Class B |
| Shock resistance | 5 g / 30 ms, 5 shocks / axis and direction acc. to IEC 61373 Category 1 Class B |

Material properties

| | |
|-----------------|-----------|
| Colour (insert) | Black |
| RoHS | compliant |
| ELV status | compliant |



Pushing Performance
Since 1945

Material properties

| | |
|-----------------------------|---------------|
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |

Specifications and approvals

| | |
|----------------|------------|
| Specifications | EN 45545-2 |
| Approvals | DNV GL |
| PROFINET | Yes |

Commercial data

| | |
|--------------------------------|--------------------------------------|
| Packaging size | 1 |
| Net weight | 17 g |
| Country of origin | Latvia |
| European customs tariff number | 85366990 |
| GTIN | 5713140224230 |
| eCl@ss | 27440291 Connector component (parts) |
| ETIM | EC002943 |
| UNSPSC 24.0 | 39121400 |