



Housing Material	Aluminium, Polycarbonate, Iron	Switching Cycles	20000
Housing Color	Silver	Power Consumption	45 kWh/1000h
Housing Surface	Brushed	Energy Efficiency Class Lightsource	This product contains light sources of energy efficiency classes E and F.
Material of Lens	Acryl		
Protection Class	Protection class I/protective grounding		
Rated Input	45 W		
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	Yes		
Control technology	Leading-edge dimmer, Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	3000/4000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	3300/3500 lm		
Rated Luminous Flux 2	3500 lm		
Light Exit Surfaces	2		
Light characteristics	Direct, Indirect		
Light direction	Top, Below		
Height	90 mm		
Diameter	400 mm		
Working Temperature	-10 to 45 °C		
Storage Temperature	-10 to 45 °C		
IP Protection Class	IP 20		
Life Time L70 / B50	30000 h		