



Little helper, big effect. With the HERCULIS display lights in a high-quality aluminium housing, you can reach all corners of a display case. To do so, the lamp head with its 40° light emission angle can be freely rotated and swivelled in any direction. In addition, the intelligent cable routing and the ready-to-use system enable easy surface and recessed mounting in display cases, counters, sales areas or in living rooms.

**Special features**

- High output with compact design
- Rotatable and swivelling heads
- For panel and surface mounting
- Intelligent cable routing
- Ready-to-use system

<b>Housing Material</b>	Die-cast aluminium
<b>Housing Color</b>	Silver
<b>Protection Class</b>	Protection class III/safety extra-low voltage
<b>Operating Mode</b>	Constant current
<b>Rated Input</b>	3 W
<b>Rated Input Voltage</b>	9 V/DC
<b>Rated Current</b>	350 mA
<b>Power Supply Unit incl.</b>	No
<b>Connection Cable Secondary</b>	Yes
<b>Secondary Connection</b>	Plug mini AMP
<b>Secondary Cable Length</b>	1 m
<b>Dimmable</b>	No
<b>Motion Detector</b>	No

<b>Working Temperature</b>	-10 to 45 °C
<b>Storage Temperature</b>	-10 to 45 °C
<b>IP Protection Class</b>	IP 20

<b>Life Time L70 / B50</b>	30000 h
<b>Switching Cycles</b>	50000
<b>Power Consumption</b>	3 kWh/1000h
<b>Energy Efficiency Class</b>	G

<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	3000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	90
<b>Rated Luminous Flux</b>	294 lm
<b>Rated Angle of Reflection</b>	30 Degree
<b>Light Distribution</b>	Symmetric
<b>Distribution Characteristic 120°</b>	DLS

<b>Swivel Angle</b>	350 Degree
<b>Light Exit Surfaces</b>	3
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Below

<b>Height</b>	250 mm
<b>Diameter</b>	39.2 mm
<b>Base height</b>	4.5 mm
<b>Base diameter</b>	39.2 mm